

特殊设备用脚轮

TP8000 系列

FEATURES

- 特征
- 顶板: 2.6t 钢板
 - 支架: 2.3t 钢板
 - 转环: 上 1/4" & 下 3/16" 钢珠
 - 旋转中心大小: Ø11.0
 - 轴: 5/16" (M8螺栓和螺母)
- 用处
- 钢琴
 - 各种设备
 - 低高度高载重脚轮

SERIES



WHEEL OPTION

HR	PLY	NYL	MIR	HDP
				
尺寸 2" (50mm)	尺寸 1 1/2" (38mm)	尺寸 1 1/2" (38mm)	尺寸 2" (50mm)	尺寸 2" (50mm)

MODEL
DESCRIPTIONS

► 单轮

 万向	 轮径(mm)	 轮宽(mm)	 轮子种类	 轴承	 承重Kg	 安装高度	 旋转半径
	轮径(mm)	轮宽(mm)					
TP8020-01-HDP	2(50)	1 11/16 (43)	重型塑料	无	90	70	47

► 双轮

 万向	 轮径(mm)	 轮宽(mm)	 轮子种类	 轴承	 承重Kg	 安装高度	 旋转半径
	轮径(mm)	轮宽(mm)					
TP8015-**-NYL PLY	1 1/2 (38)	25/32 (20)	尼龙	无	100	56	38
			聚氨酯		60		
TP8022-**-HR MIR	2 (50)	3/4 (19)	硬橡胶		90	70	47
			硬橡胶 / 塑料		65		

STEM
OPTION

轮子直径 Inch(m/m)	序号	类 型	规格 m/m
1 1/2 (40)	13	环形	Ø11 x 28mm
1 1/2 (38)	01	平板形	整体尺寸 95 x 70
			孔距 75 x 40
			安装孔尺寸 M6 (1/4")
2 (50)	01	平板形	整体尺寸 95 x 70
			孔距 75 x 40
			安装孔尺寸 M6 (1/4")
	02	平板形	整体尺寸 65 x 48
			孔距 54 x 24
			安装孔尺寸 M6 (1/4")
	11	环形	Ø11 x 38mm
	21	丝杆形	1/2" x 13 1/4" x 38mm

OPTION

AC	BO
	
红古铜	黑色氧化物